

DESTONER PULPER

with engine and emergency stop

FRUIT LINE



STANDARD FEATURES

- Inox AISI 304 frame
- Stainless steel shaft with adjustable rubber plate
- Emergency stop and CE electric panel
- Loading screw in stainless steel
- Stainless steel basket with hole 1,00-12mm

ΑΦΟΙ ΓΑΒΡΙΗΛΙΔΗ Α.Ε.Β.Ε.

Σταδίου 101, Τ.Κ. 59100 Βέροια

Τηλ. 23310 20262 Fax 23310 20263

<http://www.agroenos.com>

| MODEL | ENGINE HP (Kw) | ALIMENTATION | STONE UNLOADING HEIGHT | JUICE UNLOADING HEIGHT | LOADING HEIGHT | CAPACITY | DIMENSION | WEIGHT |
|------------|----------------|----------------------------|------------------------|------------------------|----------------|-------------|------------------|--------|
| DELTA 1 | 3 | Three-phase | 480 mm | 370 mm | 1420 mm | 1000 Kg / h | 1400x700x1420 mm | 150 Kg |
| DELTA ZERO | 1,5 | Single-phase / Three-phase | 400 mm | 300 mm | 1300 mm | 550 Kg / h | 1200x700x1300 mm | 80 Kg |
| DELTA 2 | 4 | Three-phase | 480 mm | 370 mm | 1620 mm | 2000 Kg / h | 1800x850x165 mm | 250 Kg |
| | | | | | | | | |